



#### **POST SCREW**

Material:<br/>Hot-dip galvanized steelLength:<br/>730 to 1000mmScrew diameter:<br/>68mm

SGS 70x210 68x2.0 L1000 PERFECT FOR FENCE POSTS

> **GROUND SCREWS** built for strength, designed for sustainability

#### CERTIFICATE

Material Product CE Galvanization Manufacturing process Installation process Expected min. service life\*

EN 10027-1:2016: S235 JR EN 1090 ISO 1461:2009 EN 1090 / ISO 9001:2015 ISO 9001:2015 100 years

\*StopDigging stipulates an estimated minimum lifetime for its ground screws. The amount reflects the number of years an installed screw is expected to fulfill its technical purpose under normal conditions, and is based on many years of experience and research.

CodeMark»

STOPDIC

# Perfect for fence posts, signage, and smaller structures

The SGS Post Screw provides fast and secure foundation installation without the need for concrete. With its unmatched installation speed compared to other options, this screw simplifies your construction process while delivering long-lasting durability. Post screws replace and outperform concrete plinths across a whole range of structures. They make any project faster and easier without sacrificing strength, longevity, or cost.

The U profile creates a strong bond with the supported post, with the added advantage of allowing the wood to dry properly and not decay buried in the ground.

### FIND YOUR SCREW:

Lengths ->

Model		730	1000	
70×210	68×2.0	2005	2007	
95×210	68×2.0	2006	2008	




## **SGS 70x210** 68x2.0

# **SGS 95x100** 68x2.0

Art	Comp (kN)	Tens (kN)	Lat (kN)	L (mm)	H (mm)
2005	6	4,5	3	730	280
2007	12,5	6,5	4,5	1000	280

Art	Comp (kN)	Tens (kN)	Lat (kN)	L (mm)	H (mm)
2006	6	4,5	3	730	280
2008	12,5	6,5	4,5	1000	280





MAIN OFFICE: GRUSTAGSGATAN 1B, 254 64 HELSINGBORG, SWEDEN PHONE: +46 10 - 147 07 00 | MAIL: INFO@STOPDIGGING.SE